



LED720-03AU

- Red Through Hole LED
- 720 nm, 7 mW
- AlGaAs chip, 350 x 350 μm
- 5 mm Epoxy Resin Package
- Beam Angle: $\pm 9^\circ$



Description

LED720-03Au is an AlGaInP based red LED, emitting at a peak wavelength of typically 720 nm and optical output power of 7 mW @ 20 mA. It comes in a **5 mm through hole** clear epoxy resin mold package with a beam angle of $\pm 9^\circ$. Different beam angle variants are available on request.

Maximum Ratings*

Parameter	Symbol	Values		Unit
		Min.	Max.	
Power Dissipation	P_D		180	mW
Forward Current	I_F		75	mA
Pulse Forward Current **	I_{FP}		300	mA
Reverse Voltage	V_F		5	V
Thermal Resistance	R_{THJA}		280	K/W
Junction Temperature	T_J		120	$^\circ\text{C}$
Operating Temperature	T_{CASE}	- 40	+ 100	$^\circ\text{C}$
Storage Temperature	T_{STG}	- 40	+ 100	$^\circ\text{C}$
Lead Solder Temperature ($t_{max. 3s}$)	T_{SLD}		+ 265	$^\circ\text{C}$

* Operating close to or exceeding these parameters may damage the device

** duty cycle = 1 %, pulse width = 10 μs

Electro-Optical Characteristics ($T_{CASE} = 25^\circ\text{C}$)


Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Peak Wavelength	λ_P	$I_F = 20 \text{ mA}$	710		730	nm
Half Width	λ_Δ	$I_F = 20 \text{ mA}$		23		nm
Forward Voltage	V_F	$I_F = 20 \text{ mA}$		1.7	2.3	V
	V_{FP}	$I_{FP} = 300 \text{ mA}^*$		3.7		
Total Radiated Power	P_O	$I_F = 20 \text{ mA}$		7		mW
		$I_{FP} = 300 \text{ mA}^*$		100		
Radiant Intensity	I_E	$I_F = 20 \text{ mA}$		58		mW/sr
		$I_{FP} = 300 \text{ mA}^*$		880		
Beam Angle	$2\theta_{1/2}$	$I_F = 20 \text{ mA}$		18		deg.
Rise Time	t_r	$I_F = 20 \text{ mA}$		10		ns
Fall Time	t_f	$I_F = 20 \text{ mA}$		15		ns

* duty cycle = 1 %, pulse width = 10 μs




Typical Performance Curves


Forward Current vs. Forward Voltage




Relative Radiant Intensity vs. Forward Current




Forward Current vs. Pulse Duration




Allowed Forward Current vs. Amb. Temperature



Forward Voltage vs. Ambient Temperature




Rel. Radiant Intensity vs. Ambient Temperature






Typical Performance Curves


Peak Wavelength vs. Amb. Temp.




Relative Spectral Emission



Radiation Characteristics




Radiation Characteristics



Outline Dimensions

5 mm Through Hole





General Notes

Soldering

- Do avoid overheating of the LED
- Do avoid electrostatic discharge (ESD)
- Do avoid mechanical stress, shock, and vibration
- Do only use non-corrosive flux
- Do not apply current to the LED until it has cooled down to room temperature after soldering

Cleaning

- **Cleaning with isopropyl alcohol, propanol, or ethyl alcohol is recommended**
- DO NOT USE acetone, chloroform, trichloroethylene, or MKS
- DO NOT USE ultrasonic cleaners

Static Electricity

- **LEDs are sensitive to electrostatic discharge (ESD).**
- Precautions against ESD must be taken when handling or operating these LEDs
- Surge voltage or electrostatic discharge can result in complete failure of the LED.

Radiation

- During operation these LEDs do emit light, which **could be hazardous to skin and eyes**, and **may cause cancer**.
- Do avoid exposure to the emitted light. Protective glasses if needed
- It is further advised to attach a warning label on products/systems.

Operation

- **Do *only* operate LEDs with a current source.**
- Running these LEDs from a voltage source will result in complete failure of the device.
- Current of a LED is an exponential function of the voltage across it. Usage of current regulated drive circuits is mandatory.

© All Rights Reserved

The above specifications are for reference purpose only and subjected to change without prior notice